



ORDER FORM

PYRO NEXT Light weight wheelchair

Company:

Basic price: **Pyro Next** € 718,18

Basic price: **Pyro Next with hub brake** € 899,09

Customer:

Max. capacity 125 kg

Date:

▼ Please mark!

Seat	€
Seat width in mm 400 430 460 490	<input type="radio"/>
Seat height front in mm 470 490 510	<input type="radio"/>
Seat depth 425 mm	<input checked="" type="radio"/>
Seat cushion Seat widths 370 - 490 mm	24,-
Seat upholstery, Nylon	<input checked="" type="radio"/>
Back support	
Back support height 430 mm with lumbar curve	<input checked="" type="radio"/>
Back support upholstery, Nylon	<input checked="" type="radio"/>
Handgrip elevating, removable* Pair	152,40
Head support* incl. fixation	294,-
Sidepanels	
Swing-away sidepanels with arm support	<input checked="" type="radio"/>
Leg support	
Swing-away leg support with individual footplates plastic, removable, adjustable in height	<input checked="" type="radio"/>
Leg support elevating, horizontally adjustable Pair	215,20
Leg support elevating left right	107,60
Footplate with heel strap	<input checked="" type="radio"/>
Tyres	
Rear wheel 24" x 1 3/8", PU incl. quick-release axle	<input checked="" type="radio"/>
Front wheel 8" x 1 1/4", PU	<input checked="" type="radio"/>
PU-Tyres solid rubber	<input checked="" type="radio"/>
Adapter block	<input checked="" type="radio"/>
Spoke protection, transparent 24"	145,-

* Head support and elevating handgrips cannot be mounted together

▼ Please mark!

Wheel locks	€
Knee lever wheel lock push to lock	<input checked="" type="radio"/>
Brake lever extension	29,90
Accessories	
Togo power push aid incl. mounting set	2.446,60
Mounting aid for adaptation	189,50
Anti-tip device Pair	87,50
Tilting aid	<input checked="" type="radio"/>
Safety belt	26,80
Crutch holder	23,70
Therapy tray	215,-
Oxygen/infusion holder and bracket	169,-
APINO Citybag	60,42
APINO Shopper	18,20
HERCULES padlock	10,85
Passive light	<input checked="" type="radio"/>
Frame color	
Silver Blue	<input type="radio"/>

The specified dimensions are subject to manufacturing tolerances of +/- 10 mm

Basic equipment Optional, no extra charge